

MGN4 Downlight

V48501 - V48506

Description

The MGN4 is a recessed LED circular downlight, ideal for corridors, retail and showrooms.

Environment

Indoor

Installation

Designed to recessed into ceiling

Application

For use in corridors, retail, showrooms and other similar applications.



5YR

Warranty



Protection

50,000hrs

Lifetime

General Data

Voltage	AC220-240V 50-60Hz
Power Factor	>0.9
Light Source	SMD LED
CCT	3000K/4000K
LED Lifetime	50,000hrs
Operating temp	-15°C to 25°C
Materials	Die cast aluminium body with white finish Frosted sunken glass cover

Light Data

Lumens per Watt	90-100lm/
Light Source	LED
CRI	80
Distribution	110°

MGN4 Downlight

V48501 -V48506

Product Variants

Product Code	System Power (W)	System efficacy (lm/W)	Lumens (lm)	CCT (K)	Cut-out (mm)	Diameter mm	Height mm
V48501	12W	90	1010	3000	115	130	75
V48502	12W	90	1270	4000	115	130	75
V48503	18W	90	1640	3000	165	180	80
V48504	18W	100	2040	4000	165	180	80
V48505	30W	90	2150	3000	215	215	85
V48506	30W	100	3110	4000	215	215	85

Options

OPTION	CODE
1-10V Dimming	/D
DALI Dimming	/DL
DSI Digital Dimming	/DD
Leading/Trailing Edge Dimming	/TD
3 Hour Emergency	/M3
Self Test 3 Hour Emergency	/ST

