

MGN 65

V49301/V49302/V49303/V49304

Description

A range of IP65 recessed downlights with opal polycarbonate lens.

Environment

Outdoor/Indoor

Installation

To be recessed mounted into ceiling.

Application

Exterior canopy areas, clean rooms, restrooms, laboratories and wet rooms.



General Data

Voltage	220-240V 50/60Hz
Power factor	>0.90
Light Source	SMD LED
Led Lifetime	50,000hrs/L70
Materials	Die cast aluminium body Opal polycarbonate lens

Light Data

Lumens per Watt	95-100lm/W
CRI	80
Light Source	LED
Distribution	90°

MGN 65

V49301/V49302/V49303/V49304

Product variants

Product Code	Dimensions (mm)	Cut-out (mm)	Lumens (lm)	System power	CCT
V49301	190 x 47	165-175	1500	15W	4000K
V49302	235 x 55	205-215	2550	25W	4000K
V49303	235 x 55	205-215	2400/2500/2490	25W	3CCT
V49304	235 x 55	205-215	3040/3570/3490	35W	3CCT

Options

OPTION	CODE
3 Hour Standard Emergency	/M3
3 Hour Self Test Emergency	/ST
1-10V Dimming	/D
DSI Digital Dimmable	/DD
DALI and Switch Dimmable	/DL
Trailing Edge Dimmable	/TD

