

Description

The MGGRUMB is a compact LED flood light with aesthetic design and narrow beam optics.

Environment

Outdoor

Installation

Designed to be surface mounted

Application

Suitable for façade illumination, outdoor public spaces and other similar applications



5YR

Warranty

IP65

Protection

50,000hrs

Lifetime

IK08

Toughness

General Data

Voltage	AC220-240V 50-60Hz
Power Factor	>0.95
Light Source	LED
LED Lifetime	50,000hrs/ L70B50
Operating temperature	-25°C to +40°C
Materials	Die-cast aluminium body, dark grey finish Tempered glass diffuser, impact resistant with stainless steel screws
Installation	Suitable for any horizontal or vertical surface

Light Data

Lumens per Watt	102-118lm/W
Light Source	LED
CRI	70
Optics	30°


Product Variants

Product Code	System Power (W)	System efficacy (lm/W)	Lumens (lm)	CCT (K)	Length mm	Width mm	Height mm	Weight kg
MGGRUM LED1X3800 C399 T740 L30	31.7	118	3739	4000	230	230	118	3.7
MGGRUM LED1X5300 C400 T740 L30	49.3	107	5280	4000	230	230	118	3.7
MGGRUM LED1X5900 C401 T740 L30	57.1	103	5891	4000	230	230	118	3.7
MGGRUB LED1X8400 C413 T740 L30	73.3	115	8396	4000	310	310	137	6.5
MGGRUB LED1X10600 C414 T740 L30	98.7	107	10560	4000	310	310	137	6.5
MGGRUB LED1X12000 C415 T740 L30	116.9	102	11977	4000	310	310	137	6.5

Options

Driver with DALI interface	DALI
Power reduction device with automatic reduction and middle night detection	ADIM
Louvre for better glare control for MGGRUM	D230
Louvre for better glare control for MGGRUB	D310
4000K	T840

Photometrics



Product Images

